



SRX-150 FEATURES

- “Upcut” blade rotation facilitates keeping debris out of the joint
- Triangular shaped arbor
- Blade shaft with self-aligning bearings
- Vacuum port for easy connection to dust control systems
- Remotely mounted throttle and stop switch for quick operator access
- Folding handle bar for compact transport and storage
- Poly V-belt for positive power transmission
- Easily removed blade guard cover provides quick access for blade changes and inspection
- 3-inch wide, polyurethane wheels for non-marking
- Skid plate minimizes joint chipping and spalling
- Lifting point for easy transport

Recommended Diamond Blades - Dry Cutting

GC-10 (purple)
Ultra Hard Aggregate

| Size | Part # |
|--------|--------|
| 6-3/8" | 171934 |



GC-20 (green)
Hard Aggregate

| Size | Part # |
|--------|--------|
| 6-3/8" | 171938 |



GC-30 (red)
Medium / Hard Aggregate

| Size | Part # |
|--------|--------|
| 6-3/8" | 171282 |



GC-35 (orange)
Medium Aggregate

| Size | Part # |
|--------|--------|
| 6-3/8" | 171959 |



GC-55 (yellow)
Medium / Soft Aggregate

| Size | Part # |
|--------|--------|
| 6-3/8" | 171969 |



Skid plates sold separately. Replacement stainless steel skid plate part # 171286, replacement steel skid plate part # 171283. Blades fit Soft-Cut® saws without adapters.

1315 Storm Parkway, Torrance, CA 90501 | P 800.421.5830 | F 310.539.5158

www.mkdiamond.com | customerservice@mkdiamond.com



<https://www.facebook.com/mkdiamondproducts>



<https://twitter.com/MKDiamond>

© 2019 MK Diamond Products, Inc. Soft Cut® is registered trademark of Husqvarna Construction Products. MK Diamond is not affiliated with Soft Cut®. All Rights Reserved. Images and specifications are subject to change without notice. SRX-150 Saw SS Part # AP080282 (02/19)



MK Diamond Products, Inc.



Scan for Video



SRX-150 Green Concrete Saw

Compact and lightweight, the SRX-150 dry cutting saw is engineered for early entry sawing of crack control joints within one to two hours of concrete finishing. The blade guard features a vacuum port to control dust when dry cutting. One year limited warranty.

| | |
|--------------------|-------------------|
| Engine | Honda (Gas) |
| Starter | Pull |
| Power | GX160 Cyclone |
| Blade Capacity | 6-3/8" (162 mm) |
| Depth of Cut | 1-1/8" (29 mm) |
| Arbor | Triangular |
| L x W x H (inches) | 32" x 19" x 42" |
| L x W x H (mm) | 813 x 483 x 1,067 |
| Weight | 88 lbs. (39.9 kg) |
| Includes | Skid plate |
| Part# | 172023-H |

Blade not included.

WARNING: Cancer and Reproductive Harm - www.p65warnings.ca.gov



Anti-spall, quick change skid plate



Vacuum port for easy connection to dust control systems



Folding handle bar for compact transport and storage